



EXHAUST FILTERS COLUMBUS

EUROSUPRA II & EUROSUPRA II-2M

The Eurosupra II filter is ideal for fine and dry particle overspray. It is particularly well-suited for use in horizontal flow booths. The II-2M version is even more efficient with 7 kraft paper layers and 1 polyester layer for optimal filtration.



EUROSUPRA & EUROSUPRA II-2M

Specifications	EUROSUPRA II	EUROSUPRA II-2m
Thickness	12 mm	14 mm
Weight	380 g	480 g
Retention capacity	6 to 8 kg/m ²	6.5 to 8 kg/m ²
Initial pressure drop	22.5 Pa	22.5 Pa
Maximum pressure drop	147 Pa	147 Pa
Fire resistance	M2	M2
Dimensions (Other dimensions available on request)	12 m x 1.15 m 12 m x 0.82 m 12 m x 0.73 m 12 m x 0.61 m 12 m x 0.53 m	12 m x 1.15 m 12 m x 0.82 m 12 m x 0.73 m 12 m x 0.61 m 12 m x 0.53 m
Efficiency:		
Air drying	98.5%	98.5%
Water-soluble	98.5 to 99.5%	98.5 to 99.5%
Thermosetting	98.5 to 99.5%	98.5 to 99.5%