



AIR TREATMENT FILTERS

Bag pre-filter

PSPM3

Used in air-conditioning and ventilation systems or as a pre-filter in spray booths, this pre-filter guarantees both a long lifespan and a low pressure drop.



PSPM3

APPLICATIONS:

- For ventilation and air-conditioning systems.
- Fine filtration for particles and aerosols suspended in the air.
- Large filter area, high flow rate, low initial pressure drop.
- Long lifespan.

Specifications

EN 779-2012 efficiency	G3
ISO 16890 efficiency	COARSE > 90%
Depth	360 mm, 600 mm
Frame	Galvanised
Media	Synthetic
Maximum temperature	80°C
Relative humidity	100%
Recommended final pressure	450 Pa

PSPM3

Prod. no.	Size W x L x D mm	ISO 16890 efficiency	Efficiency EN 779-2012	Number of bags	Depth mm	Filter area m ²	Rated flow rate m ³ /h	In. pressure drop	Weight
PSPM3-003/360/3-5	287 x 287 x 360	COARSE >90 %	G3	3	360	1,50	850	35	1,25
PSPM3-003/360/4-5	287 x 592 x 360	COARSE >90 %	G3	3	360	2,00	1700	35	1,50
PSPM3-002/360/5-5	490 x 592 x 360	COARSE >90 %	G3	5	360	3,00	2800	35	2,00
PSPM3-001/360/6-5	592 x 592 x 360	COARSE >90 %	G3	6	360	4,00	3400	35	2,40

Prod. no.	Size W x L x D mm	ISO 16890 efficiency	Efficiency EN 779-2012	Number of bags	Depth mm	Filter area m ²	Rated flow rate m ³ /h	In. pressure drop	Weight
PSPM3-003/600/3-5	287 x 287 x 600	COARSE >90 %	G3	3	600	2,40	850	30	1,40
PSPM3-003/600/4-5	287 x 592 x 600	COARSE >90 %	G3	3	600	3,20	1700	30	1,65
PSPM3-002/600/5-5	490 x 592 x 600	COARSE >90 %	G3	5	600	4,80	2800	30	2,30
PSPM3-001/600/6-5	592 x 592 x 600	COARSE >90 %	G3	6	600	6,40	3400	30	2,80