

QXC

This pleated filter in a galvanised or cardboard frame is fitted as standard in air handling units.



QXC

APPLICATIONS:

- For ventilation and air-conditioning systems.
- Fine filtration for particles and aerosols suspended in the air.
- Large filter area, high flow rate, low initial pressure drop.
- Long lifespan.

Specifications

EN 779-2012 efficiency	G4
ISO 16890 efficiency	90 < Am
Frame	Cardboard
Media	Cotton fibre
Maximum temperature	200°C
Recommended final pressure	250 Pa

Prod. no.	Size W x L x D mm	Efficiency EN 779-2012	Filter area m ²	Rated flow rate m ³ /h	In. pressure drop
QXC4-001/024	290 x 290 x 24	G3	0,14	850	100
QXC4-001/024	290 x 595 x 24	G3	0,28	1650	100
QXC4-001/024	395 x 495 x 24	G3	0,30	1850	100
QXC4-001/024	495 x 495 x 24	G3	0,38	2350	100
QXC4-001/024	395 x 625 x 24	G3	0,38	2350	100
QXC4-001/024	495 x 625 x 24	G3	0,48	2950	100
QXC4-001/024	495 x 595 x 24	G3	0,45	2795	100
QXC4-001/024	595 x 595 x 24	G3	0,55	3400	100